



## Rear closing by manual or electro-pneumatic roller shutter



INOGAM bodies are offered with roller shutter type rear closing, with manual or electro-pneumatic opening/closing.

The shutter (on both versions) is an assembly of pultruded metal strip. Like the surrounding body uprights and roof beam, each strip is polyurethane foam filled, for optimum insulation.

The shutter is mounted on a rear frame specifically developed for the INOGAM body, and retains all the acknowledged strength, reliability and appearance qualities of the body.

The frame angles are reinforced, which not only ensures a perfectly rigid body, it also guarantees the shutter's long-term functional strength and reliability.

The CHEREAU rear shutter concept is acknowledged as offering the best long-term performance.

Reliable

Quiet

Effortless

## Rear closing by manual or electro-pneumatic roller shutter

**33 pallets can be loaded in semi-trailers due to the increase of 50 mm in interior length!**

A top gutter channel is provided for enhanced comfort and optimum protection of the rear marker lights.



A lower cross-beam providing a substantial loading sill.

A full line of buffers under the sill, and rubber strips over the entire height, for enhanced rear end protection.



### The **manual** shutter :

The outside catch with a heavy duty hook guarantees maximum security and effectiveness.

- A rubber pad at the top of the rail prevents the blind from descending unintentionally.



### The **electro-pneumatic** shutter :

- The electric shutter up/down control (**no handle or catch**) is accessible on the right of the rear upright and in the rear overhang (optional inside the body).
- The shutter can be opened or closed, **without the slightest effort, in 18 seconds!**
- The shutter is operated by a pneumatic actuator that receives a compressed air supply from the truck or from the semi-trailer.
- Headroom under top beam is **increased by 80 mm** (in relation to the manual version).

